

Date & Time API

The `java.time` package in Java; `LocalDate/LocalTime/LocalDateTime`, `Instant`, `ZonedDateTime/OffsetDateTime`, `Duration/Period/ChronoUnit`, formatting/parsing, time zones, and migrating from legacy `Date/Calendar`.

Intermediate 55 min

Generated on 2 October 2026

Read online: <https://www.learnforgex.com/en/topics/date-time>

Date & Time API

In this lesson we'll cover Java's date/time machinery — the `java.time` package — end to end: from `LocalDate` to `Instant`, from how time zones actually work to how to interoperate with the legacy `Date / Calendar` API. Date and time looks simple at first glance but quickly gets complicated with details like time zones and Daylight Saving Time (DST) — so we'll close this lesson with a clear answer to "which class should I use, and when?"

What Is the Date & Time API?

The `java.time` package is a family of classes — all **immutable** — that represent a date, a time, a combination of the two, or a point on the timeline. The four most fundamental ones: `LocalDate` (date only), `LocalTime` (time only), `LocalDateTime` (both combined), and `Instant` (a single, unambiguous point on the universal timeline, with no time zone involved):

```
LocalDate today = LocalDate.now();           // 2026-08-10
LocalTime now = LocalTime.now();             // 14:32:07
LocalDateTime dateTime = LocalDateTime.now(); // 2026-08-10T14:32:07
Instant instant = Instant.now();              // 2026-08-10T11:32:07Z (UTC)
```

The "Local" prefix can be confusing — what's "local" here isn't the time zone a user happens to be in, it's that the class carries **no time zone information at all**. We'll see why that distinction matters in "ZonedDateTime and the Time Zone Concept."

Why Does It Exist?

A real-world example: imagine a user in Istanbul schedules a meeting for 15:00, and a participant in New York needs to see it in **their own** local time (07:00 EDT). Doing this correctly requires three separate pieces of information: an absolute point in time (the "real"

moment everyone agrees on), a time zone's rules (what local time that moment corresponds to in a given region), and a way to present both of those to the user in a readable form. The reason `java.time` splits these into separate classes is precisely to solve these three needs independently, without conflating them — we'll walk through this end to end in the first mini project.

History

Java's original date/time API (`java.util.Date` , later `Calendar`) had been around since 1996, but it carried serious design problems: `Date` was mutable, and its month values started at 0 (January = 0); the `Calendar` API was overly complex; and `SimpleDateFormat` wasn't thread-safe — we'll come back to all of these in "Migrating from the Legacy API to `java.time`." These problems were common enough complaints that Stephen Colebourne wrote the popular **Joda-Time** library; Joda-Time was successful enough that it directly inspired Java's own official standard. Oracle brought Colebourne on board to drive JSR-310, and the result shipped in Java 8 (2014) as the `java.time` package — immutable, thread-safe, and built from scratch with a clear separation of responsibilities.

LocalDate

`LocalDate` holds only a calendar date (year, month, day) — no time or time zone information:

```
import java.time.LocalDate;

class LocalDateExample {
    public static void main(String[] args) {
        LocalDate today = LocalDate.now(); // varies depending on when you run this
        System.out.println("Today: " + today);

        LocalDate fixedDate = LocalDate.of(2026, 3, 15);
        System.out.println("Fixed date: " + fixedDate);

        LocalDate nextWeek = fixedDate.plusDays(7); // returns a NEW LocalDate, doesn't
        mutate fixedDate
        System.out.println("A week later: " + nextWeek);
        System.out.println("Original unchanged: " + fixedDate);

        System.out.println("Day of week: " + fixedDate.getDayOfWeek());
        System.out.println("Is 2026 a leap year? " + fixedDate.isLeapYear());
    }
}
```

You can create a date directly with `LocalDate.of(2026, 3, 15)` , and derive new dates with methods like `plusDays(...)` — every `plus/minus` call, as with every `java.time` class, **never mutates the original**, it returns a new `LocalDate` . Methods like `getDayOfWeek()` and `isLeapYear()` handle calendar arithmetic (leap-year rules, weekdays) correctly for you — trying to compute these by hand is a well-known source of bugs.

LocalTime

`LocalTime` is `LocalDate`'s time-of-day counterpart — it holds only a time within a day (hour, minute, second, nanosecond), with no date or time zone information:

```
import java.time.LocalTime;

class LocalTimeExample {
    public static void main(String[] args) {
        LocalTime now = LocalTime.now(); // varies depending on when you run this
        System.out.println("Now: " + now);

        LocalTime openingTime = LocalTime.of(9, 0); // seconds and nanos default to 0
        System.out.println("Opening time: " + openingTime);

        LocalTime closingTime = openingTime.plusHours(8);
        System.out.println("Closing time: " + closingTime);

        System.out.println("Closing hour: " + closingTime.getHour());
        System.out.println("Is opening time before noon? " + openingTime.isBefore(LocalTime.
NOON));
    }
}
```

A call like `LocalTime.of(14, 30)` implicitly assumes zero seconds and nanoseconds.

`LocalTime`'s most typical use is expressing a recurring time that's independent of any particular date — a business rule like "opens every day at 09:00" is modeled more correctly with `LocalTime` than `LocalDateTime`, since it isn't tied to a specific calendar day.

LocalDateTime

`LocalDateTime` combines `LocalDate` and `LocalTime` — in practice it's the most commonly used `java.time` class, since most applications think about "when" as both a date and a time together:

```
import java.time.LocalDate;
import java.time.LocalDateTime;
import java.time.LocalTime;

class LocalDateTimeExample {
    public static void main(String[] args) {
        LocalDate date = LocalDate.of(2026, 3, 15);
        LocalTime time = LocalTime.of(14, 30);

        LocalDateTime combinedA = date.atTime(time);
        LocalDateTime combinedB = LocalDateTime.of(date, time);
        System.out.println("Same result either way? " + combinedA.equals(combinedB));

        System.out.println("Combined: " + combinedA);
        System.out.println("Back to date: " + combinedA.toLocalDate());
        System.out.println("Back to time: " + combinedA.toLocalTime());
    }
}
```

`LocalDate.atTime(LocalTime)` and `LocalDateTime.of(date, time)` produce the same result two different ways — which one you use depends on the pieces you already have. `toLocalDate()` and `toLocalTime()` do the reverse: pulling the pieces back out of a combined `LocalDateTime`.

Remember that `LocalDateTime` still carries **no time zone information** — a `LocalDateTime` that says "15:00" has no idea whether that's Istanbul or New York. Once you need to tie it to a time zone, move on to "ZonedDateTime and the Time Zone Concept."

Instant

`Instant` represents a single point on the UTC timeline (as seconds and nanoseconds since the January 1970 epoch) — it carries no notion of a "calendar day" or "time zone," just a **universal, unambiguous moment**:

```
import java.time.Instant;

class InstantExample {
    public static void main(String[] args) {
        Instant now = Instant.now(); // varies depending on when you run this
        System.out.println("Now: " + now);

        Instant epoch = Instant.EPOCH;
        System.out.println("Epoch: " + epoch);

        Instant fixed = Instant.ofEpochSecond(1_700_000_000L);
        System.out.println("Fixed instant: " + fixed);

        Instant later = fixed.plusSeconds(3600); // one hour later
        System.out.println("An hour later: " + later);
    }
}
```

`Instant` is ideal for machine-to-machine communication: a log entry, a database timestamp, or an event's "when did this actually happen" has exactly one correct answer with `Instant`, completely independent of which time zone it's read in. That's why, as we'll also see in "Real-World Examples: java.time in Spring Boot," storing a timestamp in a database usually means reaching for `Instant` (or a fixed-offset `OffsetDateTime`) — the user's time zone is applied only when displaying that universal moment to them.

ZonedDateTime and the Time Zone Concept

`ZonedDateTime` combines a `LocalDateTime` with a `ZoneId` (say, "Europe/Istanbul") — so it carries both "what the local clock read" and "which region's rules that should be interpreted under":

```

import java.time.LocalDateTime;
import java.time.ZoneId;
import java.time.ZonedDateTime;

class ZonedDateTimeExample {
    public static void main(String[] args) {
        LocalDateTime local = LocalDateTime.of(2026, 7, 15, 15, 0);
        ZonedDateTime istanbul = local.atZone(ZoneId.of("Europe/Istanbul"));
        System.out.println("Istanbul: " + istanbul);

        // withZoneSameInstant -- the INSTANT stays the same, the local time changes
        ZonedDateTime newYorkSameInstant = istanbul.withZoneSameInstant(ZoneId.of("America/New_York"));
        System.out.println("Same instant in New York: " + newYorkSameInstant);

        // withZoneSameLocal -- the LOCAL time stays "15:00", the instant changes
        ZonedDateTime newYorkSameLocal = istanbul.withZoneSameLocal(ZoneId.of("America/New_York"));
        System.out.println("Same local time relabeled to New York (different instant): " + newYorkSameLocal);

        System.out.println("Istanbul and 'same instant' New York represent the same instant? "
            + istanbul.toInstant().equals(newYorkSameInstant.toInstant()));
        System.out.println("Istanbul and 'same local' New York represent the same instant? "
            + istanbul.toInstant().equals(newYorkSameLocal.toInstant()));
    }
}

```

`ZoneId.of("Europe/Istanbul")` isn't a fixed number — it represents **all of a region's historical and future rules** (including DST transitions), so the same `ZonedDateTime` can correspond to a different UTC offset depending on the date. `withZoneSameInstant(...)` shows the same universal moment **in another region's local time** (the clock time changes, the instant stays the same); `withZoneSameLocal(...)` does the opposite (the clock time stays the same, the instant changes) — mixing these two up is a common source of bugs.

Calling `equals()` on a `ZonedDateTime` compares both the instant **and the time zone** — two `ZonedDateTime`s representing the exact same universal moment but expressed in different regions are **not** equal per `equals()`. If you only want to check whether they represent the same moment, use `isEqual(...)` instead.

OffsetDateTime

`OffsetDateTime` combines a `LocalDateTime` with a fixed `ZoneOffset` (say, `+03:00`) instead of a `ZoneId`. The difference is critical: a `ZoneOffset` is just a fixed number, carrying no DST transition rules — whereas a `ZoneId`, like `"Europe/Istanbul"`, represents a **region's** rules, which can change over time:

```
import java.time.LocalDateTime;
import java.time.OffsetDateTime;
import java.time.ZoneOffset;

class OffsetDateTimeExample {
    public static void main(String[] args) {
        LocalDateTime local = LocalDateTime.of(2026, 3, 15, 14, 30);

        OffsetDateTime withOffset = local.atOffset(ZoneOffset.of("+03:00"));
        System.out.println("With fixed offset: " + withOffset);

        // A ZoneOffset is just a fixed number -- it carries no DST transition rules,
        // unlike a ZoneId region such as "Europe/Istanbul".
        System.out.println("Offset: " + withOffset.getOffset());
    }
}
```

That distinction decides which one to reach for: if you want to show a user "Istanbul time," `ZonedDateTime` + `ZoneId` is the right tool (it applies DST rules automatically); if you want to store a **fixed-offset** timestamp in an API contract or a database column (the ISO-8601 `OffsetDateTime` shape), `OffsetDateTime` is more predictable — a region's rules changing in the future (say, a country dropping DST) never affects records already stored with a fixed offset.

Duration and Period

There are two ways to express the gap between two points in time, and which one you pick depends on what you're actually measuring: **Duration** represents a **time-based** amount — hours, minutes, seconds — (between `Instant`, `LocalTime`, or `LocalDateTime` values); **Period** represents a **calendar-based** amount — years, months, days — (only between `LocalDate` values):

```

import java.time.Duration;
import java.time.Instant;
import java.time.LocalDate;
import java.time.Period;

class DurationAndPeriodExample {
    public static void main(String[] args) {
        Instant start = Instant.parse("2026-01-01T09:00:00Z");
        Instant end = Instant.parse("2026-01-01T17:30:00Z");

        Duration workDay = Duration.between(start, end);
        System.out.println("Duration: " + workDay);
        System.out.println("Hours: " + workDay.toHours());
        System.out.println("Minutes: " + workDay.toMinutes());

        LocalDate projectStart = LocalDate.of(2024, 1, 10);
        LocalDate projectEnd = LocalDate.of(2026, 4, 20);

        Period projectLength = Period.between(projectStart, projectEnd);
        System.out.println("Period: " + projectLength.getYears() + " years, "
            + projectLength.getMonths() + " months, " + projectLength.getDays() + " days");
    }
}

```

`Duration.between(start, end)` gives the gap between two `Instant`s with second/nanosecond precision — a concept like "3 months" doesn't fit `Duration` at all, since months don't have a fixed length. `Period.between(start, end)` does the opposite: it produces a calendar-shaped gap like "2 years, 3 months, 10 days," but offers no hour/minute precision. Trying to use one in place of the other (say, converting a `Period` into seconds) produces meaningless results — `ChronoUnit`, which we'll see next, builds a more flexible bridge between these two worlds.

Calculating Time Differences with ChronoUnit

`ChronoUnit` is an enum that implements the `TemporalUnit` interface (recall the pattern from the Enum lesson's "Interface Implementation" section) — it offers constants like `DAYS`, `HOURS`, `MONTHS`, and lets you compute a gap as a **single raw number**, without constructing a `Duration` / `Period` object:

```
import java.time.LocalDate;
import java.time.temporal.ChronoUnit;

class ChronoUnitExample {
    public static void main(String[] args) {
        LocalDate start = LocalDate.of(2024, 1, 10);
        LocalDate end = LocalDate.of(2026, 4, 20);

        long totalDays = ChronoUnit.DAYS.between(start, end);
        long totalMonths = ChronoUnit.MONTHS.between(start, end);
        long totalYears = ChronoUnit.YEARS.between(start, end);

        System.out.println("Total days: " + totalDays);
        System.out.println("Total months: " + totalMonths);
        System.out.println("Total years: " + totalYears);
    }
}
```

Unlike `Period.between(...).getDays()`, `ChronoUnit.DAYS.between(start, end)` returns the **total** day gap (say, 400 days) as a single `long` — `Period` instead breaks that same gap into pieces, like "1 year, 1 month, 5 days." Pick based on what question you actually want answered: "how many days apart are they?" is a `ChronoUnit` question, "how much time apart, in human terms?" is a `Period / Duration` question. Another advantage of `ChronoUnit` is its generality: the same `between(...)` call works across many different types — `LocalDate`, `LocalDateTime`, `Instant`, and more.

DateTimeFormatter: Formatting and Parsing

`DateTimeFormatter` is the standard way to turn a date/time object into text (`format(...)`) or text into a date/time object (`parse(...)`) — you can use either ready-made ISO-8601 formats or define a custom pattern with `ofPattern(...)` :

```

import java.time.LocalDate;
import java.time.format.DateTimeFormatter;
import java.time.format.DateTimeParseException;

class FormattingAndParsingExample {
    public static void main(String[] args) {
        LocalDate date = LocalDate.of(2026, 3, 15);

        DateTimeFormatter formatter = DateTimeFormatter.ofPattern("dd/MM/yyyy");
        String formatted = date.format(formatter);
        System.out.println("Formatted: " + formatted);

        LocalDate parsedBack = LocalDate.parse(formatted, formatter);
        System.out.println("Parsed back: " + parsedBack);
        System.out.println("Round-trip matches original? " + parsedBack.equals(date));

        try {
            LocalDate.parse("2026-13-45"); // invalid month and day
        } catch (DateTimeParseException e) {
            System.out.println("Caught expected parse failure: " + e.getMessage());
        }
    }
}

```

`DateTimeFormatter.ofPattern("dd/MM/yyyy")` prints a `LocalDate` in a human-friendly shape like `"15/03/2026"`; the same formatter converts text back into a `LocalDate` in the other direction via `LocalDate.parse(text, formatter)`. If the text doesn't match the expected pattern (say, an invalid date like `"2026-13-45"`), a `DateTimeParseException` is thrown — this is an exception you **must** handle with a `try / catch` whenever you're processing user input.

Date Calculations

Every `java.time` class offers a set of `plus / minus` methods — `plusDays()`, `minusMonths()`, `plusYears()`, and so on — all of which preserve immutability (recall "LocalDate") and return a **new** object, never mutating the original:

```

import java.time.LocalDate;

class DateCalculationsExample {
    public static void main(String[] args) {
        LocalDate jan31 = LocalDate.of(2026, 1, 31);

        LocalDate result = jan31.plusMonths(1); // January 31 + 1 month
        System.out.println("Jan 31 + 1 month: " + result); // clamped -- 2026 is not a leap
        year

        LocalDate chained = jan31.plusYears(1).minusDays(5);
        System.out.println("Chained calculation: " + chained);
        System.out.println("Original still unchanged: " + jan31);
    }
}

```

A call like `plusMonths(1)` handles month-overflow intelligently on its own — say, January 31 plus one month doesn't land on the nonexistent "February 31," it clamps to that month's last valid day (the 28th or 29th). Chained calls (`date.plusYears(1).minusDays(5)`) are perfectly safe, since each step produces a new object — no intermediate step ever affects the one before it.

TemporalAdjusters

Some date calculations are too rule-based to express with a simple `plus / minus` — things like "the next Monday" or "the last day of this month." The `TemporalAdjusters` class offers ready-made rules (adjusters) you can pass to `with(...)` :

```
import java.time.DayOfWeek;
import java.time.LocalDate;
import java.time.temporal.TemporalAdjusters;

class TemporalAdjustersExample {
    public static void main(String[] args) {
        LocalDate date = LocalDate.of(2026, 3, 15);
        System.out.println("Starting date: " + date + " (" + date.getDayOfWeek() + ")");

        LocalDate nextMonday = date.with(TemporalAdjusters.next(DayOfWeek.MONDAY));
        System.out.println("Next Monday: " + nextMonday);

        LocalDate lastDayOfMonth = date.with(TemporalAdjusters.lastDayOfMonth());
        System.out.println("Last day of the month: " + lastDayOfMonth);

        LocalDate firstDayOfYear = date.with(TemporalAdjusters.firstDayOfYear());
        System.out.println("First day of the year: " + firstDayOfYear);
    }
}
```

`date.with(TemporalAdjusters.next(DayOfWeek.MONDAY))` computes "the first Monday after today" in a single line — doing this by hand would mean thinking through several edge cases like the number of days in the week and month boundaries. Ready-made adjusters like `lastDayOfMonth()` and `firstDayOfYear()` follow the same philosophy: they reduce common calendar rules to a single, well-tested method call instead of error-prone manual arithmetic.

Comparing Dates

Classes like `LocalDate`, `LocalDateTime`, and `Instant` offer `isBefore()`, `isAfter()`, and `compareTo()` for comparing two values — `equals()` also works, but as we saw in "ZonedDateTime and the Time Zone Concept," some types can fold extra information (like a time zone) into that comparison too:

```
import java.time.LocalDate;

class ComparingDatesExample {
    public static void main(String[] args) {
        LocalDate first = LocalDate.of(2026, 3, 15);
        LocalDate second = LocalDate.of(2026, 6, 1);

        System.out.println("first isBefore second? " + first.isBefore(second));
        System.out.println("first isAfter second? " + first.isAfter(second));
        System.out.println("compareTo: " + first.compareTo(second)); // negative -- first
        comes before second

        LocalDate sameAsFirst = LocalDate.of(2026, 3, 15);
        System.out.println("equals (value comparison): " + first.equals(sameAsFirst));
    }
}
```

`isBefore()` / `isAfter()` are far more readable than writing `compareTo() < 0` — the code reads almost like English for "is this date before that one?" For `LocalDate` and `LocalDateTime`, `equals()` already compares only the value (field by field, much like the auto-generated `equals()` we saw in the Record lesson) — the exception you actually need to watch for is `ZonedDateTime`, covered in the previous section.

Migrating from the Legacy API to java.time

You may still run into `java.util.Date`, `Calendar`, and `SimpleDateFormat` in older codebases — all three have the serious problems we touched on in "History," but for situations you can't fully avoid (say, a third-party library that still hands you a `Date`), there are conversion bridges:

```
import java.time.Instant;
import java.time.ZoneId;
import java.time.ZonedDateTime;
import java.util.Date;

class LegacyInteropExample {
    public static void main(String[] args) {
        Date legacyDate = new Date(1_700_000_000_000L); // old API, milliseconds since epoch

        Instant instant = legacyDate.toInstant(); // lossless -- Date is just an epoch
        timestamp underneath
        System.out.println("Converted to Instant: " + instant);

        ZonedDateTime inIstanbul = instant.atZone(ZoneId.of("Europe/Istanbul"));
        System.out.println("Viewed in Istanbul: " + inIstanbul);

        Date backToLegacy = Date.from(instant); // bridging back, for an old API that still
        needs a Date
        System.out.println("Round-trip matches original? " + backToLegacy.equals
        (legacyDate));
    }
}
```

`Date.toInstant()` converts an old `Date` into a modern `Instant` — since `Date` itself is internally nothing more than an epoch timestamp, this conversion is lossless. `Instant.atZone(zoneId)` builds the bridge in the other direction. The most critical warning is about `SimpleDateFormat`: this class is **not thread-safe** — multiple threads sharing the same `SimpleDateFormat` instance (recall "Race Conditions" from the Threads lesson) can produce corrupted results; `DateTimeFormatter` is immutable and can be safely shared across threads.

New code should never start with `Date`, `Calendar`, or `SimpleDateFormat` — these should only ever be used to bridge at the boundary with an older API (a third-party library, an old database driver). We'll emphasize this rule again in "Common Mistakes."

Time Zones and Daylight Saving Time

Time zones are this lesson's most overlooked, yet most bug-prone, topic. **UTC** (Coordinated Universal Time) is the fixed reference point every time zone is measured against; **GMT** shares practically the same offset as UTC but is historically based on a different definition. Region identifiers like `"Europe/Istanbul"` and `"America/New_York"` don't represent a fixed offset at all — they carry rules that can **change over time**, most notably Daylight Saving Time (DST):

```
import java.time.ZoneId;
import java.time.ZonedDateTime;

class TimeZoneAndDstExample {
    public static void main(String[] args) {
        // Istanbul stopped observing DST in 2016 -- fixed at UTC+3 year round.
        ZonedDateTime istanbulWinter = ZonedDateTime.of(2026, 1, 15, 12, 0, 0, 0, ZoneId.of(
("Europe/Istanbul")));
        ZonedDateTime istanbulSummer = ZonedDateTime.of(2026, 7, 15, 12, 0, 0, 0, ZoneId.of(
("Europe/Istanbul"));
        System.out.println("Istanbul winter offset: " + istanbulWinter.getOffset());
        System.out.println("Istanbul summer offset: " + istanbulSummer.getOffset() + "
(same -- no DST anymore)");

        // New York still observes DST -- the offset differs between winter and summer.
        ZonedDateTime newYorkWinter = ZonedDateTime.of(2026, 1, 15, 12, 0, 0, 0, ZoneId.of(
("America/New_York")));
        ZonedDateTime newYorkSummer = ZonedDateTime.of(2026, 7, 15, 12, 0, 0, 0, ZoneId.of(
("America/New_York"));
        System.out.println("New York winter offset: " + newYorkWinter.getOffset());
        System.out.println("New York summer offset: " + newYorkSummer.getOffset() + "
(different!)");
    }
}
```

DST transitions produce two odd situations: on the day clocks spring forward, some local times **never happen at all** (say, 02:30 is skipped straight to 03:30); on the day clocks fall back, some local times happen **twice**. `ZonedDateTime` resolves these ambiguities for you

with an automatic rule — but not knowing that rule exists leads to surprising bugs like "why does this date show a 25-hour day?" A concrete example from Turkey: the "Europe/Istanbul" region stopped observing Daylight Saving Time in 2016 and has stayed fixed at UTC+3 year-round ever since — solid proof that `ZoneId` rules really can change over time.

Real-World Examples: `java.time` in Spring Boot

`java.time` shows up in almost every layer of a modern Spring Boot application. On the JSON side, Spring Boot's default Jackson configuration automatically registers the `jackson-datatype-jsr310` module — so an `Instant` or `LocalDate` field serializes to ISO-8601 text (like "2026-08-10T11:32:07Z") with no extra annotations needed. On the database side, Hibernate has natively supported `java.time` types since 5.2 — an `Instant` field on a JPA `@Entity` maps directly onto PostgreSQL's time-zone-aware `timestampz` column:

```
import java.time.Instant;
import java.time.LocalDate;

class Event {
    private final String name;
    private final Instant createdAt; // absolute timestamp -- what Jackson/Hibernate map
    automatically
    private final LocalDate eventDate; // calendar date -- no time zone needed for "which
    day"

    Event(String name, Instant createdAt, LocalDate eventDate) {
        this.name = name;
        this.createdAt = createdAt;
        this.eventDate = eventDate;
    }

    @Override
    public String toString() {
        return name + " (created " + createdAt + ", scheduled for " + eventDate + ")";
    }
}

class EventExample {
    public static void main(String[] args) {
        Event event = new Event(
            "Java Meetup",
            Instant.parse("2026-03-01T10:15:30Z"),
            LocalDate.of(2026, 4, 12)
        );

        System.out.println(event);
        // In a real Spring Boot app, this exact class (with @Entity/@JsonFormat added)
        // would serialize createdAt as ISO-8601 JSON and map to a PostgreSQL timestampz
        // column -- no special handling needed for the java.time types themselves.
    }
}
```

The `Event` class holds its `Instant createdAt` and `LocalDate eventDate` fields with no framework annotations at all — and that's the whole point: framework integration doesn't live in the class itself, it lives in the fact that the framework **already understands** these types. The exact same `Event` class could become a JPA `@Entity` or a Jackson DTO, and the field types (`Instant` , `LocalDate`) would never need to change — because both Hibernate and Jackson understand them out of the box.

Best Practices

- Store timestamps in a database as `Instant` (or a fixed-offset `OffsetDateTime`), and convert to `ZonedDateTime` only when displaying to a user — as we noted in "Instant," this eliminates time zone ambiguity at the earliest possible point.
- Always use `ZonedDateTime` (or at least a known `ZoneId`) when showing a date/time to a user — a bare `LocalDateTime` never answers the question "in which time zone?" (see the warning in "LocalDateTime").
- When choosing between `Duration` / `Period` / `ChronoUnit` , ask what you're actually measuring: a time-based span (`Duration`), a calendar-based range (`Period`), or a single raw number (`ChronoUnit`) (see "Duration and Period" and "Calculating Time Differences with ChronoUnit").
- Never start new code with `Date` , `Calendar` , or `SimpleDateFormat` — use them only to bridge at the boundary with an old API (see "Migrating from the Legacy API to java.time").
- Always handle `DateTimeParseException` when parsing a date from user input — an invalid date string is an inevitability, not an edge case (see "DateTimeFormatter: Formatting and Parsing").

Common Mistakes

- 1. Treating `LocalDateTime` as if it knew a time zone.** `LocalDateTime` never carries time zone information — if you need to show a user an unambiguous moment, use `ZonedDateTime` or `Instant` instead (see the warning in "LocalDateTime").
- 2. Comparing two `ZonedDateTime` s with `equals()` and assuming they represent the same moment.** `equals()` also compares the time zone — to compare only the instant, use `isEqual(...)` (see the warning in "ZonedDateTime and the Time Zone Concept").
- 3. Sharing a single `SimpleDateFormat` instance across multiple threads.** This class isn't thread-safe and produces corrupted results; `DateTimeFormatter` safely replaces it (see "Migrating from the Legacy API to java.time").
- 4. Assuming a time zone's rules (especially DST) never change.** As the "Europe /Istanbul" example shows, a region's DST rules can change completely over the years (see "Time Zones and Daylight Saving Time").

5. Trying to use `Period` for an hour/minute-precision calculation. `Period` is calendar-based only (years/months/days); for time-based gaps use `Duration`, and for a single raw number use `ChronoUnit` (see "Duration and Period").

Summary, Cheat Sheet, and Glossary

`java.time` has been Java's immutable, thread-safe date/time API, built with a clear separation of responsibilities, since Java 8. Key takeaways:

- `LocalDate` / `LocalTime` / `LocalDateTime` carry no time zone information at all — the word "Local" emphasizes exactly that
- `Instant` is a single, unambiguous point on the UTC timeline — ideal for machine-to-machine communication and database timestamps
- `ZonedDateTime` carries a `ZoneId` (a region's rules, including DST); `OffsetDateTime` carries only a fixed `ZoneOffset`
- `Duration` is time-based, `Period` is calendar-based, and `ChronoUnit` expresses the gap between two points as a single raw number
- `DateTimeFormatter` handles both formatting and parsing, and is thread-safe
- Every `plus` / `minus` call returns a new object, never mutating the original
- `TemporalAdjusters` offers ready-made adjusters for rule-based calculations like "the next Monday"
- `Date` / `Calendar` / `SimpleDateFormat` should only be used to bridge with legacy APIs — `SimpleDateFormat` is not thread-safe
- Store `Instant` / `OffsetDateTime` in your database, display `ZonedDateTime` to users

Quick reference:

```
// Core classes
LocalDate date = LocalDate.now();           // date only
LocalTime time = LocalTime.now();           // time only
LocalDateTime dateTime = LocalDateTime.now(); // date + time, no time zone
Instant instant = Instant.now();             // a single point on the UTC timeline

// Time zones
ZonedDateTime zoned = ZonedDateTime.now(ZoneId.of("Europe/Istanbul"));
OffsetDateTime offset = OffsetDateTime.now(ZoneOffset.of("+03:00"));

// Measuring gaps
Duration duration = Duration.between(instant1, instant2); // hours/minutes/seconds
Period period = Period.between(date1, date2);              // years/months/days
long days = ChronoUnit.DAYS.between(date1, date2);         // a raw number

// Formatting / parsing
DateTimeFormatter fmt = DateTimeFormatter.ofPattern("dd/MM/yyyy");
String text = date.format(fmt);
LocalDate parsed = LocalDate.parse(text, fmt);

// Calculations and TemporalAdjusters
LocalDate nextMonday = date.with(TemporalAdjusters.next(DayOfWeek.MONDAY));
LocalDate endOfMonth = date.with(TemporalAdjusters.lastDayOfMonth());

// Legacy bridge
Instant fromLegacy = legacyDate.toInstant();
Date toLegacy = Date.from(instant);
```

Glossary

LocalDate / LocalTime / LocalDateTime — Immutable classes carrying no time zone information, representing a date, a time, and the combination of the two, respectively.

Instant — An immutable class representing a single, unambiguous point on the UTC timeline.

ZonedDateTime — Combines a local date/time with a **ZoneId** that carries a region's full set of rules, including DST.

OffsetDateTime — Combines a local date/time with a fixed **ZoneOffset** that carries no DST rules.

Duration — A time-based amount expressing the gap between two points in hours/minutes/seconds.

Period — A calendar-based amount expressing the gap between two dates in years/months/days.

ChronoUnit — An enum implementing **TemporalUnit**, used to express the gap between two points as a single raw number.

DateTimeFormatter — A thread-safe class used to convert date/time objects to text (formatting) and text back into date/time objects (parsing).

TemporalAdjusters — A helper class offering ready-made adjusters for rule-based date calculations like "the next Monday" or "the last day of the month."

DST (Daylight Saving Time) — The practice, in some regions, of moving clocks forward /backward during certain parts of the year; the primary reason **ZoneId** rules can change over time.

Appendix: Mini Project — A Multi-Time-Zone Meeting Scheduler

In this mini project we build the scenario described in "Why Does It Exist?": a scheduler that stores a meeting as a single absolute moment (**Instant**) and can display it in any time zone you ask for:

```
import java.time.Instant;
import java.time.ZoneId;
import java.time.ZonedDateTime;

class MeetingScheduler {
    private final String title;
    private final Instant scheduledAt; // single source of truth -- an unambiguous instant

    MeetingScheduler(String title, Instant scheduledAt) {
        this.title = title;
        this.scheduledAt = scheduledAt;
    }

    ZonedDateTime viewIn(ZoneId zone) {
        return scheduledAt.atZone(zone);
    }

    String getTitle() {
        return title;
    }
}
```

```

import java.time.Instant;
import java.time.ZoneId;
import java.time.ZonedDateTime;

class MeetingSchedulerDemo {
    public static void main(String[] args) {
        MeetingScheduler meeting = new MeetingScheduler(
            "Sprint Planning",
            Instant.parse("2026-07-15T12:00:00Z")
        );

        ZonedDateTime inIstanbul = meeting.viewIn(ZoneId.of("Europe/Istanbul"));
        ZonedDateTime inNewYork = meeting.viewIn(ZoneId.of("America/New_York"));
        ZonedDateTime inTokyo = meeting.viewIn(ZoneId.of("Asia/Tokyo"));

        System.out.println(meeting.getTitle() + " local times:");
        System.out.println("  Istanbul: " + inIstanbul);
        System.out.println("  New York: " + inNewYork);
        System.out.println("  Tokyo: " + inTokyo);

        // All three represent the exact same instant, just expressed differently.
        boolean sameInstant = inIstanbul.toInstant().equals(inNewYork.toInstant())
            && inNewYork.toInstant().equals(inTokyo.toInstant());
        System.out.println("Same instant everywhere? " + sameInstant);
    }
}

```

`MeetingScheduler` holds the meeting's moment as nothing but an `Instant` — as we emphasized in "Instant," this single source of truth carries no time zone ambiguity at all. The `viewIn(ZoneId)` method converts that `Instant` into the requested region's `ZonedDateTime`; `MeetingSchedulerDemo` shows what local time the same meeting corresponds to **simultaneously** in Istanbul, New York, and Tokyo — all three print a different clock time, yet all three point at the exact same `Instant`.

It's no accident that all three cities in `MeetingSchedulerDemo` have different UTC offsets — seeing that Istanbul no longer observes DST (recall "Time Zones and Daylight Saving Time"), while New York still does, makes concrete exactly why a `ZoneId`'s rules are specific to a single region.

Appendix: Mini Project — Event Duration Tracking

Our last mini project combines the ideas from "Migrating from the Legacy API to `java.time`" and "Duration and Period": a tracker that converts `Date`-based records coming from an old system into `Instant` and computes their duration:

```

import java.time.Duration;
import java.time.Instant;
import java.util.Date;

class EventDurationTracker {
    private final String name;
    private final Instant start;
    private final Instant end;

    EventDurationTracker(String name, Instant start, Instant end) {
        this.name = name;
        this.start = start;
        this.end = end;
    }

    static EventDurationTracker fromLegacyDates(String name, Date legacyStart, Date
legacyEnd) {
        // Bridging old java.util.Date records into the modern API -- lossless,
        // because a Date is already just an epoch timestamp underneath.
        return new EventDurationTracker(name, legacyStart.toInstant(), legacyEnd.
toInstant());
    }

    Duration duration() {
        return Duration.between(start, end);
    }

    String getName() {
        return name;
    }
}

```

```

import java.time.Duration;
import java.util.Date;

class EventDurationTrackerDemo {
    public static void main(String[] args) {
        // A modern record, created directly with Instant.
        EventDurationTracker modern = new EventDurationTracker(
            "Modern Conference",
            java.time.Instant.parse("2026-05-01T09:00:00Z"),
            java.time.Instant.parse("2026-05-01T17:00:00Z")
        );

        // A "legacy" record, as if it came from an old system using java.util.Date.
        Date legacyStart = new Date(1_700_000_000_000L);
        Date legacyEnd = new Date(1_700_010_800_000L);
        EventDurationTracker legacy = EventDurationTracker.fromLegacyDates("Legacy
Workshop", legacyStart, legacyEnd);

        for (EventDurationTracker tracker : new EventDurationTracker[] { modern, legacy }) {
            Duration d = tracker.duration();
            System.out.println(tracker.getName() + ": " + d.toHours() + "h " + (d.
toMinutes() % 60) + "m");
        }
    }
}

```

`EventDurationTracker.fromLegacyDates(...)` converts two `java.util.Date`s coming from a legacy API into modern `Instant`s via `toInstant()` — a real application of the bridge we saw in "Migrating from the Legacy API to `java.time`." The `duration()` method then uses `Duration.between(...)` to compute the event's total length in hours and minutes; `EventDurationTrackerDemo` shows that records coming from both the old and the new API can be processed by the same `EventDurationTracker` without any friction.

The reason `fromLegacyDates(...)` uses `Date.toInstant()` is that `Date` itself **already** carries nothing but an epoch timestamp — so the conversion is always safe and lossless. But converting from `Calendar` may also require accounting for its time zone information — a more advanced topic we didn't cover in "Migrating from the Legacy API to `java.time`."